

DATASHEET APSYN420
Specification V1.49

10 MHz to 20 GHz Wideband Synthesizer



Document size:

1 title page
8 content pages

DEFINITIONS

The specifications in the following pages describe the warranted performance of the instrument for 23 ±5 °C after a 30-minute warm-up period

Typical: Expected mean values, not warranted performance

Min and max: Parameter range that is guaranteed by product design, and/or production tested. Warranted performance specifications include guard-bands to account for the expected statistical performance distribution, measurement uncertainties, and changes in performance due to environmental conditions.

INTRODUCTION

Ultra-compact, fast and low power consumption Frequency Synthesizer with USB & LAN interface

The APSYN420 is a wideband low phase-noise synthesizer operating from 10 MHz to 20 GHz. The nominal output power is +23 dBm.

The module has a mili-Hz frequency resolution and uses a high-stability internal reference. The internal reference can be phase-locked to a user-settable external reference. For highest phase coherence, multiple APSYN420s can be cascaded with just one master reference clock.

The APSYN420 offers dedicated sweeping capabilities with switching speeds of only 25 μs and wideband frequency modulation as well as narrow pulse modulation.

The module has USB and LAN interfaces and can be controlled using the SCPI 1999 command set. Operated with an external 6V DC supply, it consumes less than 10 watts.

FACTS & FIGURES & SPECIFICATIONS

Signal Specifications

PARAMETER	MIN	TYPICAL	MAX	NOTE
Frequency Range	10 MHz		20 GHz	
Resolution		0.001 Hz		
Phase Resolution		0.1 deg		
Switching Speed		1.5 ms		after SCPI command received
CW Mode		180 µs		
Sweep / List Mode		25 µs		Option FS
SSB Phase noise at 1 GHz				(see also plot)
at 1 kHz from carrier		-118 dBc/Hz		
at 100 kHz from carrier		-128 dBc/Hz		
Wideband noise		-150 dBc/Hz		
SSB Phase noise at 10 GHz				
at 1 kHz from carrier		-100 dBc/Hz		
at 100 kHz from carrier		-108 dBc/Hz		
Wideband noise		-150 dBc/Hz		
Output power	18 dBm	23 dBm	26 dBm	(see plot)
Reverse Power Protection				
DC Voltage		7 V		
RF Power			23 dBm	
Output impedance		50 Ohms		
VSWR		1.8		
Spectral purity				
Output harmonics		-15 dBc		
Sub-harmonics		-75 dBc	-60 dBc	
Non-harmonic spurious		-75 dBc	-60 dBc	

Modulation Capabilities

PARAMETER	MIN	TYPICAL	MAX	NOTE
Pulse Modulation				
Modulation source		Internal/ External		
Pulse rise/fall time		7 ns		
On/off ratio	30 dB	45 dB		Pout > +10 dBm
Pulse overshoot			10%	
Pulse delay		20 ns		
Pulse polarity	1V	2V TTL		AC coupled DC coupled
External input threshold	0.85 V	0.9 V	0.95 V	TTL compatible
External input voltage range	-0.5 V		+5.5 V	TTL compatible
External input hysteresis		60 mV		
Internal pulse generator				
Repetition frequency (PRF)	0.1 Hz		10 MHz	= 1/T
Duty cycle	1 % to 99 % in 1% steps			within specified minimum pulse width
Pulse Width settling range	30 ns		1 s	
Pulse Pattern Modulation & Staggered PRF				Using internal pattern generator
Programmable pattern length	2		4192	
Pulse width resolution		15 ns		
Pulse jitter		2 ns	10 ns	
Polarity		Normal, inverse		selectable
Frequency Modulation				
Modulation source		Internal		
Maximum Frequency deviation (peak)		N · 500 MHz		< 1.25 GHz (N=1) 1.25 GHz to 2.5 GHz (N=0.125) 2.5 GHz to 5 GHz (N=0.25) 5 GHz to 10 GHz (N=0.5) 10 GHz to 20 GHz (N=1) 20 GHz to 40 GHz (N=2)
Deviation accuracy		0.50%	2%	
Distortion (THD)		< 1 %		1 kHz rate, 10 kHz deviation
Modulation rate	0.1 Hz		800 kHz	3dB
Modulation waveforms	Sine			
Phase Modulation				
Modulation source		Internal		
Phase deviation (peak)	0		100 · N· rad	
Deviation accuracy		0.50%	2%	
Modulation rate	0.1 Hz		800 kHz	
Modulation waveforms		Sine		
Distortion (THD)		< 1%		1 kHz rate & N x rad deviation
Frequency Chirps		Linear, ramp, up/down		
Modulation source		Internal		
Bandwidth			10%	
Dwell time	1 ns		10 ms	
Slope	0.1 Hz		100 MHz / µs	

Sweeping Capability, Sweep type: linear, logarithmic, random

PARAMETER	MIN	TYPICAL	MAX	NOTE
Frequency Sweep				
Step time (t_{step})	180 µs 25 µs			Option FS
Dwell time (t_{dwell})	15 µs			

Frequency Reference


PARAMETER	MIN	TYPICAL	MAX	NOTE
Internal reference frequency		100 MHz		
Internal Reference Output Frequency				
Temperature stability			±100 ppb	0 to 50 degC
Aging 1st year		0.5 ppm	1 ppm	
Aging per day			5 ppb	after 30 days operations
Warm-up time		5 min		
Output of internal reference		100 MHz		
Output power	0 dBm	5 dBm		
Output impedance		50 Ohms		
Bypass Internal reference Input		100 MHz		High phase synchronous mode
Phase Lock to External Reference	1 MHz	integer MHz	250 MHz	
Reference input level	-5 dBm	0 dBm	+13 dBm	
Reference Bypass Mode	5 dBm		+15 dBm	
External Reference Lock Range				
1-250 MHz			±1.0 ppm	
Bypass 100 MHz			>100 ppm	
Reference input impedance		50 Ohms		

Trigger (TRIG IN): Input is TRIG IN at front panel


PARAMETER	MIN	TYPICAL	MAX	NOTE
Trigger Types				Continuous, single (point), gated, gated direction
Trigger Source				external, bus (LAN, USB)
Trigger Modes				Continuous free run, trigger and run, reset and run
Trigger uncertainty		5 µs		
External Trigger delay	50 µs		40 s	
External Delay Resolution		15 ns		
Trigger Modulo	1		255	Execute only on Nth trigger event
Trigger Polarity		Rising, falling		
External trigger input threshold	0.85 V	0.9 V	0.95 V	TTL compatible
External trigger input voltage range	-0.5 V		+5.5 V	TTL compatible
External trigger input hysteresis		60 mV		

TYPICAL PERFORMANCE CURVES


Phase Noise Performance



Output Power 0.01 to 20 GHz



Pulse Modulation (20 ns width, 100 ns period)



ORDERING INFORMATION

HOST MODEL	PRODUCT	DESCRIPTION
APSYN420	**APSYN420**	20 GHz Synthesizer, flange-mount module
APSYN420	**Option 1URM**	19 inch 1HU rackmount enclosure
APSYN420	**Option FS**	Ultra fast switching speed
APSYN420	**Option GPIB**	GPIB interface (only with option 1URM)

GENERAL CHARACTERISTICS

Remote programming interfaces

Ethernet 100BaseT LAN interface, USB 2.0 host & device, Control language SCPI Version 1999.0

Power requirements 6V VDC; 20 W maximum


Mains adapter supplied: 100-240 VAC in/ 6 V 6.0 A DC out

Environmental (Levels similar to MIL-PRF-28800F Class 3/4)
Environmental stress Samples of this product have been type tested to be robust against the environmental stresses of storage, transportation, and end-use; those stresses to temperature, humidity, shock, vibration, altitude, and power line conditions.
Operating temperature range 0 to 45 °C
Storage temperature range –40 to 70 °C
Operating and storage altitude up to 15,000 feet (4600 m)

CE **notice**

Safety/EMC complies with applicable Safety and EMC regulations and directives.

Weight ≤ 1.0 kg (2.2 lbs) net
Dimensions 24 x 10.5 x 6 cm
Dimensions 21 x 10.5 x 6 cm
24 x 10.5 x 6 cm (with option FS)



Front view



Rear view

Document History

Version/Status	Date	Author	Notes
V147	2019-03-01	jk	New layout
V148	2019-03-27	mm	Correction: Frequency Reference Out-put power
V149	2021-02-25	db	Pulse and trigger input electrical specifications

AnaPico Inc. of Switzerland

Europastrasse 9
8152 Glattbrugg
Switzerland

Phone +41 44 440 00 50
Email sales@anapico.com

www.anapico.com
www.anapico.com/downloads/

NOTES